

AXIS Camera Station S2212 Appliance

All-in-one recorder with PoE switch for UHD surveillance

AXIS Camera Station S2212 Appliance is an all-in-one recording solution with integrated, manageable PoE switch designed to deliver reliable high-definition surveillance with up to 4K resolution. For quick and easy installation, AXIS S2212 is preconfigured and preloaded with AXIS Camera Station video management software, and includes licenses for 12 channels plus all necessary system software. AXIS Camera Station offers an intuitive user interface that allows users to take full advantage of Axis wide range of video surveillance cameras and other IP products. With the operating system stored on a solid-state drive (SSD) and 5-year warranty, AXIS S2212 provides a reliable surveillance solution.

- > [All-in-one solution with integrated PoE switch](#)
- > [High-definition surveillance with up to 4K resolution](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)



AXIS Camera Station S2212 Appliance

Licenses	12 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	Playback: Supports the same split scenarios as live view Supports only one monitor Playback at high speeds can affect video performance.
System scalability	Qualified for up to 12 video channels and 24 doors	Recording
Hardware		General
Processor	Intel® Core™ i3	Operating system
Memory	8 GB	Microsoft® Windows® 10 IoT Enterprise Operating system recovery: yes Operating system drive: 120 GB SSD
Storage	Surveillance Class HDD Total HDD slot: 2 Free HDD slot: 1 Out-of-the-box storage: 6 TB (1x6 TB)	Security
Switch	12 ports integrated, 135 W total power budget Power over Ethernet (PoE) IEEE 802.3at Class 4	Security support for encrypted operating system drive and recording drive FIPS 140-2 level 2 certified Trusted Platform Module (TPM 2.0)
Graphics card	Intel® HD Graphics	Operating conditions
Power	Max 270 W, 135 W PoE dedicated 100 - 240 V AC, 3.5 A, 50/60 Hz 54 V DC, 5 A External power adapter	0 °C to 40 °C (32 °F to 104 °F) Humidity: 10-90% RH (non-condensing)
Connectors	Front side: 1x USB 3.0 1x Audio line in 1x Audio line out Rear side Switch: 12x PoE ports 10/100 Mbps 1x SFP 10/100/1000 Mbps 1x RJ45 10/100/1000 Mbps Rear side Server: 1x RJ45 10/100/1000 Mbps 2x USB 2.0 1 Displayport™ 1 HDMI port	Storage conditions
Video		-40 °C to 65 °C (-40 °F to 149 °F)
Video streaming	Live view: 1 x 4K stream full screen 4 split x 1080p Up to 12 cameras split view Supports two monitors, maximum one 4K monitor recommended	Approvals
		EMC CNS 13438, EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN 60950-1, IEC/EN 62368-1, KC-Mark, UL 62368-1, IS 13252
		Dimensions
		330 x 230 x 78 mm (13 x 9.1 x 3.1 in)
		Weight
		5.8 kg (12.8 lb)
		Included accessories
		Rack ears, power adapter
		Optional accessories
		Surveillance Hard Drive 6 TB available from Axis AXIS TS2901 Appliance Stand Axis desktop terminals Axis Ethernet surge protector For more accessories, see axis.com
		Warranty
		Recorder and hard drive: 5-year warranty, see axis.com/warranty

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com